



# AUSBOND AA-20

## Technical Data Sheet

### Description

AUSBOND AA-20 formulated from USP GRADE WHITE MINERAL OILS which are colorless tasteless and odorless. AUSBOND AA-20 is also U.S.D.A. H-1 RATE and KOSHER approved, which gives them full acceptability for use in all areas where incidental food contact may occur.

### Typical Uses

AUSBOND AA-20 is a special lubricant for universal application in foods industry such as chains, bearing, slides, guides, hinges, handles, links, ect. Pharmaceuticals-release agent for tables, Punch & Die, Food-baking, pan oil, defoamers. Plasticizers and internal lubricants, extrusion aids.

### Advantages

- NSF/U.S.D.A. H-1 \*Registered
- Excellent anti-wear and anti-rust
- Excellent load-carrying properties
- Minimize contamination problems
- Formulated from USP White mineral oil
- Extend equipment life

**This Product also available in aerosol cans.**

### Specification

	ASTM Test	-----Bright and Clear-----			
		32	46	68	100
Appearance	VISUAL				
ISO Grade					
Pour Point °C	D-97	-15	-15	-15	-15
Flash Point, °C	D-92	228	235	242	247
Viscosity, cSt@ 40 °C	D-445	28.22	50.63	70.37	90.43
Viscosity, SUS@ 100 °F	D-2161	154.2	200.5	350.7	450.5
Refractive Index @40 °C	D-2140	1.469	1.467	1.474	1.478
Color, Saybolt	D-156	+30	+30	+30	+30
Specific Gravity @ 15/4 °C	D-1298	0.85	0.87	0.87	0.88